

STEEL.



BEN^R

Certification	DIN EN 397		
Protective properties	<ul style="list-style-type: none"> metal spatter (MM) lateral deformation (LD) 		
internal equipment			
Type	I/79 GD-R		
Special feature	-		
Webbing	6 point		
Version	with screw cap		
Eye protection	-		
Sweat band	real leather		
Cushion strip	standard		
Chin strap suspension	4 point		
helmet features			
Series	<ul style="list-style-type: none"> rain gutter 		
Factory fitted option	<ul style="list-style-type: none"> 16 mm double slots side ventilation (adjustable) hole in visor headtorch bracket cable loop all-round reflective film 		
Accessories	<ul style="list-style-type: none"> face protection neck protection hearing protection chin strap sweat bands reflective film 		
version			
Size	1	2	3
Head circumference	52 – 56cm	53 – 61cm	59 – 63cm
Colours	-	natural fibre special metallic colours	-
Branding	printed		
Item Size	Front 2,3 x 3 cm	Side 9 x 3 cm	
parameter			
Shape	straight		
Material	PF-SF (textile phenol)		
Weight	approx. 410 g		

APPLICATIONS

- hot environments
- chemical industry
- workplaces with high UV exposure
- workplaces with demanding and varied protection requirements
- high performance all-round helmets
- dockyards



Benefits

- suited to tasks with exposure to molten metal, for example
- high lateral stiffness
- rain gutter
- retains shape at elevated temperatures
- high penetration resistance and impact toughness
- chemical resistant
- highly resistant to aging (long service life)
- very comfortable to wear and secure fit due to ergonomically formed height-adjustable internal fittings
- natural fibre appearance



SCHUBERTH