

SPECIAL SOLUTIONS.



CLIMBING HELMET

Certification	DIN EN 397		
Protective properties	<ul style="list-style-type: none"> ▪ Lateral deformation (LD) 		
internal equipment			
Type	I/79 GD-R		
Special feature	-		
Webbing	6 point		
Version	with screw closure		
Eye protection	possible		
Sweat band	real leather		
Cushion strip	Special		
Chin strap suspension	4 point		
Helmet features			
Series	<ul style="list-style-type: none"> ▪ side ventilation (adjustable) ▪ short visor ▪ polystyrene inner shell ▪ 4 point chin strap 		
Factory fitted option	<ul style="list-style-type: none"> ▪ integrated eye protection (only helmet size 2) ▪ headtorch bracket ▪ cable loop ▪ all-round reflective film 		
Accessories	<ul style="list-style-type: none"> ▪ eye protection screen ▪ neck protection ▪ hearing protection ▪ chin strap ▪ sweat band ▪ all-round reflective film 		
version			
Size	1	2	3
Head circumference	52 – 56 cm	53 – 61 cm	59 – 63 cm
Colours		■ RAL 9016	
Branding	printed		
Item Size	Front 2,3 x 3 cm	Side 9 x 3 cm	
parameter			
Shape	straight		
Material	UP-GF (Polyester fibreglass)		
Weight	approx. 405 g		

APPLICATIONS

- scaffolding
- tower climbers
- free-climbers



Benefits

- **High lateral stiffness**
- **Increased shock absorption** from integrated polystyrene inner shell
- Retains shape at elevated temperatures
- High penetration resistance and impact toughness
- Chemical resistant
- Highly resistant to aging (long service life)
- Very comfortable to wear and secure fit due to ergonomically formed height-adjustable internal fittings
- with short visor and 4 point chin strap



SCHUBERTH