

CHEMICAL. OIL. GAS.

CROSS® GUARD

Certification	DIN EN 397		
Protective properties	<ul style="list-style-type: none"> protective property down to -20°C 		
internal equipment			
Type	I/79 G-R		
Special feature	-		
Webbing	6 point		
Version	with screw closure		
Eye protection	-		
Sweat band	Wellvitex® Z+		
Cushion strip	standard		
Chin strap suspension	4 point		
helmet features			
Series	<ul style="list-style-type: none"> MFA-Tech side ventilation (adjustable) 		
Factory fitted option	<ul style="list-style-type: none"> without side ventilation (Cross@Electric) eye protection 		
Accessories	<ul style="list-style-type: none"> face protection neck protection chin strap sweat bands reflective film adapter for lamp lamp eye protection 		
version			
Size	1	2	3
Head circumference	52 – 56 cm	53 – 61 cm	59 – 63 cm
Colours	-	<ul style="list-style-type: none"> RAL 9016 RAL 1023 RAL 5017 RAL 3020 RAL 6024 RAL 2009 custom colours 	-
Branding	printed		
Item Size	Front 6 x 4,5 cm	Side 9 x 2 cm	
parameter			
Shape	straight		
Material	PE (Polyethylene)		
Weight	approx. 395 g		

APPLICATIONS

- Cold operations
- Chemical and petrochemical industry
- Assembly work



Design example with optional reflective film.



Benefits

- **Protective property down to -20°C**
for use in low temperatures (e.g. outdoors in very cold conditions)
- Easy handling of the accessories due to MFA-Tech multifunction adapter
- Standard with adjustable side ventilation
- Very comfortable to wear and secure fit due to ergonomically formed height-adjustable internal fittings
- Low weight
- Comprehensive selection of accessories
- By default with corrugated Wellvitex® Z+ sweat band and screw closure

THERMO
PLAST



SCHUBERTH