

MINING.

MINE RESCUE TEAM HELMET

Certification	DIN EN 397		
Protective properties	<ul style="list-style-type: none"> ▪ Lateral deformation (LD) 		
	internal equipment		
Type	I/79 G-R		
Special feature	-		
Webbing	6 point		
Version	with screw closure		
Eye protection	possible		
Sweat band	real leather		
Cushion strip	Standard		
Chin strap suspension	4 point		
	helmet features		
Series	<ul style="list-style-type: none"> ▪ hole in visor ▪ headtorch bracket ▪ cable loop ▪ all-round reflective film ▪ rain gutter 		
Factory fitted option	<ul style="list-style-type: none"> ▪ side ventilation (adjustable) ▪ all-round reflective film 		
Accessories	<ul style="list-style-type: none"> ▪ chin strap ▪ sweat bands ▪ reflective film 		
	version		
Size	1	2	3
Head circumference	52 – 56 cm	53 – 61 cm	59 – 63 cm
Colours	-	■ RAL 2009	-
Branding	-		
Item Size	-	-	-
	parameter		
Shape	straight		
Material	UP-GF (Polyester fibreglass)		
Weight	approx. 400 g		

APPLICATIONS

- Mine rescue



Benefits

- **High lateral stiffness**
- Retains shape at elevated temperatures
- High penetration resistance and impact toughness
- Chemical resistant
- Highly resistant to aging (long service life)

DURO
PLAST



SCHUBERTH