

STEEL.




SUP

Certification	DIN EN 397		
Protective properties	<ul style="list-style-type: none"> Temperatures up to +150 °C (only when used in conjunction with special internal fittings I/79 GW-R) metal spatter (MM) 		
internal equipment			
Type	I/79 GD-R	I/79 GW-R	
Special feature	–	tested to supplementary requirement +150 °C	
Webbing	6 point	6 point	
Version	with screw cap	with screw cap (flame retardant)	
Eye protection	–	–	
Sweat band	real leather	real leather	
Cushion strip	standard	standard	
Chin strap suspension	4 point	4 point	
helmet features			
Series	–		
Factory fitted option	<ul style="list-style-type: none"> side ventilation (adjustable) all-round reflective film 		
Accessories	<ul style="list-style-type: none"> neck protection chin strap sweat bands all-round reflective film 		
version			
Size	1	2	3
Head circumference	52 – 56cm	53 – 61cm	59 – 63cm
Colours	–	<ul style="list-style-type: none"> RAL 9016 special metallic colours 	–
Branding	printed		
Item Size	Front 4,5 x 4,5 cm	Side 9 x 3 cm	
parameter			
Shape	with a wide continuous brim		
Material	UP-GF (Polyester fibreglass)		
Weight	approx. 445 g		

APPLICATIONS

- hot environments
- chemical industry
- workplaces with high UV exposure
- workplaces with demanding and varied protection requirements
- high performance all-round helmets



Benefits

- Suited for tasks carried out in high ambient temperatures (e.g. furnaces)
- suited to tasks with exposure to molten metal, for example
- protection due to wide continuous brim
 - retains shape at elevated temperatures
- high penetration resistance and impact toughness
- chemical resistant
- highly resistant to aging (long service life)
- very comfortable to wear and secure fit due to ergonomically formed height-adjustable internal fittings



SCHUBERTH